			INFO	MATION	REPORT			
OUNTRY	/ f:	SSR				DATE DIS	STR. /4 Sep	1951
UBJECT			Markings				PAGES 1	
	. •					NO. OF E	ENCLS	
LACE CQUIRE	.D					(LISTED BEL		,**
ATE CQUIRE ATE OF						SUPPLEN REPORT		50X1-HUN
OF THE UNIT	TED STATES AND 32. AS ENTS IN A	WITHIN THE I AMENDED. IT BY MANNER TO	N AFFECTING THE NATIONAL IERANING OF THE ESPIONAL STRANSMISSION OR THE R AN UMAUTHORIZED PERSC THIS FORM IS PROMISITE	GE ACT 50 EVELATION DN IS PRO-	THIS IS U	NEVALUATEC	) INFORMATION	N 50X1-HUN
•	3.	the door which are about the condition the wire cation. The original lister corner on the corner of	and another to 1/4" to 3/2 and another to 3/2 and size of a restal flap. Beluctor comprese into one pichat the seal gin of the fred with white of the car so covered. The	in the latch.  16". The conductive I. The not hends of the sees the wire see. The join and the door seight is indicated that when the markings are	A piece of wi uctor puts the ame of the state wire go throu with a key and ing is not for have at the en t ated on the sea side of the car door is opened low, so that the	re is draw wire in a ion and the gh a slot this action strength, ampered with. The definition in a spect, the dest	n through the lead seal when the lead not	e holes ich is pressed seal. ss welds an indi- the car one ings will
•	3.	the door which are about the condition the section of the condition of the condition of the corner o	and another to 1/4" to 3/2 and another the seal of the car so covered. The com the ground	in the latch.  16". The conductive I. The north ends of the sees the wire see. The join and the door eight is indicated that when the markings are d.	A piece of winctor puts the ame of the state wire go throuwith a key and ing is not for have the seaside of the cardoor is opened	re is draw wire in a ion and the gh a slot this actio strength, ampered with the definition of the destination of the destinati	n through the lead seal when the lead in the lead in more or lead to the lead in the lead	e holes ich is pressed seal. ss welds an indi- the car one ings will
• .	3.	the door which are about the condition the section of the condition of the condition of the corner o	and another to 1/4" to 3/2 and another the seal of the car so covered. The com the ground	in the latch.  16". The conductive I. The north ends of the sees the wire see. The join and the door eight is indicated that when the markings are d.	A piece of wi uctor puts the ame of the state wire go throught with a key and ing is not for have the teen to atted on the sea side of the car door is opened low, so that the	re is draw wire in a ion and the gh a slot this actio strength, ampered with the definition of the destination of the destinati	n through the lead seal when the lead in the lead in more or lead to the lead in the lead	e holes ich is pressed seal. ss welds an indi- the car one ings will about
•	3.	the door which are about the condition the section of the condition of the condition of the corner o	and another 1/4" to 3/2 e size of a real flap. Be suctor comprese into one pichat the seal gin of the freed with white of the car so covered. The com the groum is indicated	in the latch.  16". The conducted. The north ends of the sees the wire see. The join and the door eight is indicachalk on the that when the markings are d.  in the same s	A piece of wi uctor puts the ame of the state wire go throught with a key and ing is not for have the teen to atted on the sea side of the car door is opened low, so that the	re is draw wire in a ion and the gh a slot this actio strength, ampered with the desire a spect, the dest ley can be	n through the lead seal when the lead in the lead in more or lead to the lead in the lead	e holes ich is pressed seal. ss welds an indi- the car one ings will about